

Scientific & Technical Gases Ltd

20DA- 20 LITRE ALUMINIUM NON-REFILLABLE CYLINDER

CONTENTS

20 Litres

SERVICE PRESSURE

20 bar (300psi)

DIMENSIONS

Height 250 mm, Diameter 78 mm

WEIGHT

0.32 kg

CYLINDER MATERIAL

Aluminium

Valve connection - screw thread

STANDARDS

NPL, UKAS or NIST standards.
Manufactured gravimetrically
to ISO 6142

EQUIPMENT

- Special regulator required for 20 litre cylinders
- Regulators include:
 - On/off valve with mini flow meter
 - Septum type for syringe use
 - Balanced flow regulator

WARRANTY

Non-reactive gases	24 months
H ₂ S mixtures	6 months
SO ₂ mixtures	6 months
4 gas mixtures (H ₂ S)	6 months

MIXTURE TOLERANCES

Minor components are certified to the following analytical tolerance

2-20ppm = +/- 10%

21- 50ppm = +/- 5%

51-300ppm = +/- 2%



Units 1&2 Speedwell Road,
Parkhouse Industrial Estate,
Newcastle under Lyme,
Staffordshire, United Kingdom,
ST5 7RG

TEL: +44 (0) 1782 566897

FAX: +44 (0) 1782 564906

EMAIL: info@stgas.eu

WEBSITE: www.stgas.eu

**WORLDWIDE
SUPPLIER OF
QUALITY GAS
PRODUCTS
AND SERVICES**