

Scientific & Technical Gases Ltd

60DA- 60 LITRE ALUMINIUM NON-REFILLABLE CYLINDER

CONTENTS

60 Litres

SERVICE PRESSURE

34 bar (500psi)

DIMENSIONS

Height 365 mm, Diameter 90 mm

WEIGHT

0.75 Kg

CYLINDER MATERIAL & VALVE

Aluminium

Connection C10 valve (5/8"-18)

STANDARDS

NPL, UKAS or NIST standards.
Manufactured gravimetrically
to ISO 6142

EQUIPMENT

- Cylinder valve compatible with all major manufacturers regulators
- Fixed flow regulators available at 0.5, 1.0, 2.5 and 3.0 LPM
- On-Demand Flow Regulator (ODFR for non-reactive, H₂S and SO₂ mixtures)
- Dial-a-flow regulator (non-reactive gases)

WARRANTY

| | |
|--|-----------|
| Non-reactive gases | 36 months |
| Ethanol | 12 months |
| H ₂ S, SO ₂ and 4 gas mixtures | 12 months |
| NO, NH ₃ , HCN, ETO | 12 months |
| Cl ₂ (min 5ppm) | 9 months |
| HCl (min 5ppm) | 8 months |
| NO ₂ | 6 months |

MIXTURE TOLERANCES

Minor components are certified to the following analytical tolerance

2-20ppm = +/- 10%

21- 50ppm = +/- 5%

51-300ppm = +/- 2%



Units 1&2 Speedwell Road,
Parkhouse Industrial Estate,
Newcastle under Lyme,
Staffordshire, United Kingdom,
ST5 7RG

TEL: +44 (0) 1782 566897

FAX: +44 (0) 1782 564906

EMAIL: info@stgas.eu

WEBSITE: www.stgas.eu

**WORLDWIDE
SUPPLIER OF
QUALITY GAS
PRODUCTS
AND SERVICES**